

IP Camera ST-IPC8200F



Pixel - 200W Pixel
Image Sensor - 1/2.5" CMOS
Min. Illumination - IR ON 0Lux
Lens - HD 6MM
Lens interface - CS
Day&Night - IR-CUT
Video Compression - H.264 High Profile, JPEG Screenshot
Main/Extra Stream - 1080P/D1
Video output bitrate - 32Kbps-16Mbps
Audio Compression - G.711a
Max. Resolution - 1920*1080
"Frame Rate - 25fps (1920*1080)
Image Setting - Saturation, Brightness, Contrast adjustable
through Client software or web server
Storage - network storage
Intelligent Alarm - Motion detect, Video loss, Network
disconnection, IP address conflict,
Storage full, Storage error
Protocol - TCP/IP,HTTP,DHCP,DNS,DDNS, PPPoE,SMTP,
NTP ,RTSP
Basic - Reset button, Anti-flicker, Dual stream, Heartbeat,
Password protection
NVR/HVR - Yes
Mobile monitor - Yes
Communication Interface - 1pc RJ45 10M/100M
self-adaptive Ethernet interface, 1pc
WIFI wireless network interface
Video Output - 1Vp-p Composite Output(75Ω/BNC)
Operating Condition - 10°C~60°C, Humidity 90% or
less(non-condensing)
Power Supply - DC12V±10%
Power Consumption - 6W MAX;
Protection - Range
Led - 30pcs φ5 LEDs, IR distance 30M

www.beloteks.lv