

3 STRAND  
TWISTED ROPE

# POLYPROPYLENE

EXCELLENT RESISTANCE TO CHEMICALS, FLOATING ON WATER, HARD TO THE TOUCH, EASY MAINTENANCE, NOT HARMFUL TO HEALTH.

## TYPE A

dia  
2.5–40 mm



## APPLICATIONS

- ▶ **FISHING ROPES**
- ▶ **AUXILIARY ROPES**
- ▶ **MOORING ROPES**
- ▶ **TOWING ROPES**

## PARAMETERS

Material	PP split film
Specific Gravity	0.91 kg/dm <sup>3</sup>
Floating	yes
Melting temperature	165 °C
UV resistance	average
Abrasion resistance	average
Standard	ISO EN 1346 PP2
Water absorption	max. 0.1 %
Dry and wet conditions	identical wet and dry conditions



TYPE A	Diameter		Weight		Strength MBL	
	mm	inch	kg/100 m	t	kN	
	2.5	1/3	0.40	0.2	2.0	
	4	1/2	0.72	0.4	3.8	
	6	3/4	1.63	0.7	7.0	
	8	1	2.89	1.2	11.6	
	10	1 1/4	4.52	1.8	17.2	
	12	1 1/2	6.51	2.5	24.2	
	14	1 3/4	8.86	3.3	32.4	
	16	2	11.60	4.2	41.4	
	18	2 1/4	14.60	5.3	51.9	
	20	2 1/2	18.10	6.4	62.8	
	22	2 3/4	21.90	7.7	75.2	
	24	3	26.00	9.0	88.3	
	26	3 1/4	30.60	10.5	102.5	
	28	3 1/2	35.40	12.0	117.6	
	30	3 3/4	40.70	13.6	133.3	
	32	4	46.30	15.3	150.1	
	36	4 1/2	58.60	19.1	187.0	
	40	5	72.30	23.3	228.5	