




FTP 4Pairs Cat.5e – LSZH (CPR-Dca)



Construction:

- 1 – Jacket
- 2 – Shield – foil
- 3 – Drain wire
- 4 – Protective skin
- 5 – Solid twisted pair

Description:

Shielded Copper cable, 4 pairs, category 5e, solid
 Shield: Aluminum foil
 Cable is used for indoor installation.
 Meets: ISO/IEC11801, TIA/EIA-568-C.2

Materials:

Conductor: Solid Bare Copper 0.50±0.005 mm (24 AWG)
 Conductor insulation: HDPE, diameter 1.00 ± 0.03 mm
 Identification: - Blue-White/Blue, - Orange-White/Orange, - Green-White/Green, - Brown-White/Brown
 4 twisted pairs
 Jacket: White FR-LSZH (Dca, s2, d2, a1) (RoHS Complied)

Technical characteristics:

Outer cable diameter: 5.0 ± 0.4 mm
 Jacket thickness: 0.50 ± 0.04 mm
 Installation temperature: 0°C – +50°C
 Operating temperature: -20°C – +60°C
 Standard package: 305 m, Carton Box

Electrical characteristics (100m):

FREQUENCY (MHz)	RL ≥ dB	ATT ≤ dB	NEXT ≥ dB	DELAY ≤ ns	IMPEDANCE (OHMS)	PSNEXT ≥ dB	ELFEXT ≥ dB	PSELFEXT ≥ dB
1	20.0	2.0	65.3	570.00	100±15	62.3	63.8	60.8
4	23.0	4.1	56.3	552.00	100±15	53.3	51.8	48.8
8	24.5	5.8	51.8	546.73	100±15	48.8	45.7	42.7
10	25.0	6.5	50.3	545.38	100±15	47.3	43.8	40.8
16	25.0	8.2	47.2	543.00	100±15	44.4	39.7	36.7
20	25.0	9.3	45.8	542.05	100±15	42.8	37.8	34.8
25	24.3	10.4	44.3	541.20	100±15	41.3	35.8	32.8
31.25	23.6	11.7	42.9	540.44	100±15	39.9	33.9	30.9
62.5	21.5	17.0	38.4	538.55	100±15	35.4	27.9	24.9
100	20.1	22.0	35.3	537.60	100±15	32.3	23.8	20.8

www.beloteks.com

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Beloteks Latvia SIA products is indicative only and shall not be binding on Beloteks Latvia SIA or be treated as constituting a representation on the part of Beloteks Latvia SIA.