




UTP 4Pairs Cat.5e PE – Outdoor



Construction:

- 1 – Outer Jacket
- 2 – Twisted pair
- 3 – Rip-cord

Description:

Unshielded Copper cable, 4 pairs, category 5e, solid
 Cable is used for outdoor installation.
 Meets: ISO/IEC11801, TIA-568C.2, YD/T1019

Materials:

Conductive material: wire made of soft annealed electrolytic copper.
 Conductor insulation: HDPE.
 The cable jacket: black LDPE (complies RoHS)

Technical characteristics:

Conductor diameter: 0.50 mm ± 0.005 mm (24 AWG)
 Insulated conductor diameter: 0.88 ± 0.05 mm
 Outer cable diameter: 5.2 ± 0.4 mm
 Jacket thickness: 0.55 mm ± 0.05 mm
 Minimum bend radius: 8 outer cable diameters
 Installation temperature: -5°C – +50°C
 Operating temperature: -30°C – +60°C
 Standard package: 305 m, Carton box

Electrical characteristics:

FREQUENCY (MHz)	ATTENUATION dB/100m MAX	NEXT dB MIN	PS-NEXT dB MIN	ELFEXT dB MIN	PS-ELFEXT dB MIN	IMPEDANCE (OHMS)	RL dB MIN	DELAY ns MAX
1	3.0	60.0	57.0	58.6	55.6	100±15	19.0	521
4	3.9	54.8	51.8	46.6	43.6	100±15	19.0	504
10	6.2	48.5	45.5	38.6	35.6	100±15	19.0	498
16	7.9	45.2	42.2	34.5	31.5	100±15	19.0	496
20	8.9	43.7	40.7	32.6	29.6	100±15	19.0	495
25	10.0	42.1	39.1	30.7	27.7	100±15	18.0	495
31.25	11.2	40.5	37.5	28.7	25.7	100±15	17.1	494
62.5	16.2	35.7	32.7	22.7	19.7	100±15	14.1	492
100	21.0	32.3	29.3	18.6	15.6	100±15	12.0	491

www.beloteks.com

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Beloteks Latvia SIA products is indicative only and shall not be binding on Beloteks Latvia SIA or be treated as constituting a representation on the part of Beloteks Latvia SIA.